



ACT
CHINA
晶莹化工

GrateClean™ 510

网格板清洗剂

HMIS 2,1,0

Product: GrateClean™ 510 Grate Cleaner is a powerful cleaner that can handle the toughest cleaning assignments. This product is thickened to provide maximum dwell time on vertical surfaces such as oven walls, substructure beams, and grates. It is used in-situ to soften and remove paint overspray from the paint shop floor and floor grates, prior to washing. With extended dip exposures, this product will also remove cured paint. It is designed to wash away completely with a fresh water rinse.

产品: GrateClean™ 510 网格板清洗剂为强效清洁剂，能处理最顽固的清洁任务。增稠的配方延长了表面浸透时间，可垂挂于烘房墙壁，基梁和网格板盖。主要用于喷房地面和网格板，在清洗之前去除油漆过喷。增加剥漆效果。可以当场使用软化网格板或地面的油漆。浸泡更长时间，还可清除工装夹具上的固化油漆。该产品用水就可以完全冲洗净。



Benefits: Water-based formula.
Neutral pH- non hazardous for transport
Powerful cleaning ability. Great for oven walls.
High flashpoint for safety.
Thickened for maximum dwell time on vertical services.
Emulsifies in water allowing for quick cleanup with minimal effect on sludge system.

优点: 水性配方
PH值中性，运输安全。
强效清洗，适合喷房墙面。
安全高闪点
粘稠配方，延长浸透时间，适用于垂直表面
遇水乳化，便于清洗，对水循环系统增加的负荷小



ACT
CHINA
晶莹化工

GrateClean™ 510

网格板清洗剂

HMIS 2,1,0

Usage:

- Spot test this material in an inconspicuous area to check for deleterious effects prior to wide spread use.
- Use GrateClean™ 510 at full strength concentrations. Mix thoroughly before using. Apply by hand or medium pressure pump.
- Allow product to remain for 5-15 mins before rinsing completely with pressure wash.
- Brushing or rubbing (e.g. broom) after the first several minutes will greatly improve performance for heavy overspray buildup.



ACT
CHINA
晶莹化工

GrateClean™ 510

网格板清洗剂

HMIS 2,1,0

- 用法:**
- 先进行小范围测试，确定对所清洗的表面无损害。
 - 直接使用，不可稀释。使用前搅拌或摇晃均匀。可手工涂抹或中等压力泵喷涂。
 - 等待 5—15 分钟后用压力水完全冲洗干净。
 - 在一开始几分钟内用铁刷或其他摩擦可以很大程度地去除固化油漆。

Safety: Be sure to use all applicable safety precautions. Safety glasses, gloves, and skin protection are recommended. Work in well-ventilated areas.

安全: 该产品为腐蚀性化学品。操作时请确认使用所有适用的防护措施，包括防护眼镜、手套、皮肤保护。

Packaging: 25kg Pail
包装: 25 公斤小桶