



ACT
CHINA
晶莹化工

OvenClean™ 212K

水性剥漆膏

HMIS 2,1,0

Product: OvenClean™ 212K Waterbased Paint Strip Gel tackles the toughest cleaning tasks. It is thickened to provide maximum dwell time on vertical surfaces such as oven walls, substructure beams, and grates. It is used to remove oven varnish buildup but can also be used in-situ to soften and remove paint overspray from the paint shop floor and grates prior to washing. It can be easily rinsed away with low-pressure water.

产品: OvenClean™ 212K 剥漆膏为强效清洁剂，能处理最顽固的清洁任务。增稠的配方延长了表面浸透时间，可垂挂于烘房墙壁，基梁和网格板盖。主要用于困难的烘房清洁中，甚至可用于喷房地面和网格板，在清洗之前去除油漆过喷。增加剥漆效果。另外可以当场使用软化网格板或地面的油漆。浸泡更长时间，还可清除工装夹具上的固化油漆。该产品用水就可以完全冲洗净。



Benefits: Powerful cleaning ability. Great for oven walls.
Waterbased formulation for safety. No flashpoint.
Thickened for maximum dwell time on vertical services.
Emulsifies in water allowing for quick cleanup with minimal effect on sludge system.

优点: 强效清洗，适合喷房墙面。
安全水性产品。
粘稠配方，延长浸透时间，适用于垂直表面
遇水乳化，便于清洗，对水循环系统增加的负荷小



ACT
CHINA
晶莹化工

OvenClean™ 212K

水性剥漆膏

HMIS 2,1,0

- Usage:** -Spot test to check for deleterious effects prior to widespread use. This product should not be used on plastics, and vinyl, and soft metals such as aluminum and galvanized coatings.
-Use at full strength. Mix thoroughly before using. Apply manually or with spray pump.
-Allow product to remain for 5-15 mins before rinsing completely with pressure wash.
-Brushing or rubbing (e.g. broom) after the first several minutes will greatly improve performance for heavy overspray buildup.
- 用法:** -先进行小范围测试，确定对所清洗的表面无损害。该产品不可用于塑料和乙烯表面。使用在类似铝和铁皮等软金属表面也要小心。
-直接使用，不可稀释。使用前搅拌或摇晃均匀。可手工涂抹或等压力泵喷涂。
-等待 5—15 分钟后用压力水完全冲洗干净。
- 在一开始几分钟内用铁刷或其他摩擦可以很大程度地去除固化油漆。
- Safety:** ActoClean™ 212 is a corrosive. Be sure to use all applicable safety precautions. Safety glasses, gloves, and skin protection are recommended. Work in well-ventilated areas.
- 安全:** 该产品为腐蚀性化学品。操作时请确认使用所有适用的防护措施，包括防护眼镜、手套、皮肤保护。
- Packaging:** 25kg Pail, 25 公斤小桶
- 包装:**